



The gauge that set the standard: Original Stewart Warner Deluxe™

For over 40 years, Stewart Warner Deluxe™ instruments have set the standard for automotive gauges, with a classic and timeless look that includes the famous SW block logo—your symbol of excellence! From the first Shelys to Daytonas to muscle cars and street rods, Deluxe™ gets the job done. And, it remains our most popular line!

Features include:

- Bold, easy-to-read, black-on-white graphics that tell you right away it's a Stewart Warner Deluxe™ gauge!
- Polished stainless steel, low-profile bezel
- Original white pointer with black hub
- Wide range of mechanical and electrical instruments
- 2-5/8" gauges also available



Deluxe™: The standard for over 40 years!



Deluxe™ : Tachometers & Speedometers



Type	Range	3-3/8"		Note:	Additional Kit Needed:
		Mech	Elec		
Speedometer	0-120 MPH	-	82896	Programmable/ Odometer	82527 or 82646
	0-160 MPH	550BP-D	-		
	180-0 MPH	550ABE	-	Counter Clockwise/ Odometer	411335-D (counter clockwise adapter)
	0-140 KPH	82697	-	Programmable/ Odometer	
	0-140 KPH	-	82656	Programmable/ Odometer	114878 or 82646
Tachometers	5,000 RPM	551AKM-D	-	.5:1 Ratio	
	9,000 RPM	535AH-D	-	.5:0 Ratio	
	6,000 RPM	-	82162B	4-, 6-, 8-Cyl	
	6,000 RPM	-	82162	4-, 6-, 8-Cyl; 12 Pole	
	8,000 RPM	-	82170	4-, 6-, 8-Cyl; 12 Pole	
	8,000 RPM	-	82163	4-, 8-, 12-Cyl; 20 Pole	
5"					
Speedometer	0-160 MPH	-	82698	Programmable/Odo	114878 or 82646
Tachometer	10,000 RPM	-	82699	Ignition coil	

Kits include: Mounting hardware, light kit (bulb & socket), installation instructions. Purchase senders separately.



550ABE
Reverse speedometer



82162B



82162B



82170



82692

Deluxe™ : 2-5/8" Gauges



Type	Range	2-5/8"		Note:	Additional Kit Needed:
		Mech	Elec		
Air Pressure	10-100 psi	82408	-		114840 (6 ft. tube) or 114841 (16 ft. tube)
Ammeter	60-0-60	-	82404	Internal Shunt	
Fuel Level	240 Ohm	-	82413		
Fuel Pressure	1-15 psi	82405	-		114840 (6 ft. tube) or 114841 (16 ft. tube)
Oil Pressure	5-100 psi	82406	-		114840 (6 ft. tube) or 114841 (16 ft. tube)
	10-100 psi	82407	-		
Oil Temperature	140-325°F	82410-60	-	60" capillary	
	140-325°F	82410-72	-	72" capillary	
	140-325°F	82410-96	-	96" capillary	
Water Temperature	100-265°F	82409-60	-	60" capillary	
	100-265°F	82409-72	-	72" capillary	
	100-265°F	82409-144	-	144" capillary	
Vacuum	0-30 Hg	82411	-		114842

Kits include: Mounting hardware, light kit (bulb & socket), installation instructions. Purchase senders, tubing or shunts separately.

2-5/8" DELUXE™ CHROME PANEL				
Panel/Type	Range(s)	Kit Number:	Notes:	Also Included in Kit:
Triple Panel				
Fuel Pressure/ Oil Pressure/ Water Temperature	1-15 psi/ 5-100 psi/ 100-265°F	82221	Mechanical	2 ea. of 6 ft. tubing kit 72" cap. on Water Temp ga.

Kits includes: Mounting panel and hardware, light kit installation instructions and additional accessories as indicated above.



82309



82307



82303



82304



82322



82308



82327-72



82323



82329



82328



82311



82306



82326



82305

Deluxe™ : 2-1/16" Gauges



Type	Range	2-1/16"		Note:	Additional Kit Needed:
		Mech	Elec		
Air Pressure	10-150 psi	82329	-		114840 (6 ft. tube) or 114841 (16 ft. tube)
	0-150 psi	-	82346		279C
Ammeter	30-0-30	-	82310	Internal Shunt	
	60-0-60	-	82311	Internal Shunt	
	100-0-100	-	82313	Internal Shunt	
	100-0-100	-	82343	Reqs. Shunt	407616
Boost	0-30/0-15	82340	-	Red Pointer	
Exhaust Temp	300-1500°F	-	82335		See probes Page 53
Fuel Level	240 Ohm	-	82303		Senders Page 48
	90 Ohm	-	82341		Senders Page 48
	73 Ohm	-	82342		Use OE sender
Fuel Pressure	0-16 psi	-	82333		114874
	1-10 psi	82319	-		Use braided stainless steel hose. Gauge must be mounted outside pas- senger compartment
	2-30 psi	82320	-		
	10-200 psi	82325	-		
Manifold Pressure	2-30 psi	82321	-		
Oil Pressure	0-80 psi	-	82304		279A
	0-100 psi	-	82305		114875
	5-80 psi	82322	-		114840 (6 ft. tube) or 114841 (16 ft. tube)
	5-100 psi	82323	-		
	10-200 psi	82324	-		
Oil Temperature	100-280°F	-	82115		280ED-F
	140-320°F	-	82308		280EE-F
	140-325°F	82327-60	-	60" capillary	
	140-325°F	82327-72	-	72" capillary	
	140-325°F	82327-96	-	96" capillary	
	140-325°F	82327-144	-	144" capillary	
Trans. Temperature	150-325°F	-	82344		280EE-F
Water Temperature	100-240°F	-	82306		280EA
	100-280°F	-	82307		280ED-F
	100-265°F	82326-60	-	60" capillary	
	100-265°F	82326-72	-	72" capillary	
	100-265°F	82326-96	-	96" capillary	
	100-265°F	82326-120	-	120" capillary	
	100-265°F	82326-144	-	144" capillary	
Vacuum	0-30Hg	82328	-		114842
Voltmeter	10-16V	-	82309	Color Band	
	10-16V	-	82391	Color Band	
	20-32V	-	82347	Color Band	

Kits include: Mounting hardware, light kit (bulb & socket), installation instructions. Purchase senders, tubing or shunts separately.

Deluxe™ : Metric



Type	Range	2-1/16"		Note:	Additional Kit Needed:
		Mech	Elec		
Air Pressure	70-1000 kPa	82393			114840 (6 ft. tube) or 114841 (16 ft. tube)
	0-1000 kPa		82388		279C
Ammeter	30-0-30		82310	Internal Shunt	
	60-0-60		82311	Internal Shunt	
	100-0-100		82313	Internal Shunt	
	100-0-100		82343	Reqs. Shunt	407616
Fuel Level	240 Ohm		82303		114876
	90 Ohm		82341		439361-F or 439362-F
	73 Ohm		82342		Use OE sender
Oil Pressure	0-700 kPa		82387		114875
Oil Temperature	60-160°C	82395-72		Tube - 1.83m	
	60-160°C	82395-96		Tube - 2.44m	
	60-160°C	82395-144		Tube - 3.66m	
	60-160°C		82390		280EE-F
Water Temperature	40-130°C	82394-72		Tube - 1.83m	
	40-130°C	82394-96		Tube - 2.44m	
	40-130°C	82394-144		Tube - 3.66m	
	40-115°C		82389		280EC
Voltmeter	10-16V		82309	Color Band	
	10-16V		82391	Color Band	
	20-32V		82347	Color Band	

Kits include: Mounting hardware, light kit (bulb & socket), installation instructions. Purchase senders, tubing or shunts separately.

Type	Range	3-3/8"		Note:	Additional Kit Needed:
		Mech	Elec		
Speedometer	0-140 KPH	82697		Odometer	
	0-140 KPH		82656	Odometer	114878 or 82646
Tachometers	5,000 RPM	551AKM-D		.5:1 Ratio	
	9,000 RPM	535AH-D		.5:0 Ratio	
	6,000 RPM		82162B	4-, 6-, 8-Cyl	
	6,000 RPM		82612	4-, 6-, 8-Cyl; 12 Pole	
	8,000 RPM		82170	4-, 6-, 8-Cyl; 12 Pole	
	8,000 RPM		82163	4-, 8-, 12-Cyl; 20 Pole	

Kits include: Mounting hardware, light kit (bulb & socket), installation instructions. Purchase senders separately.

Deluxe™ : Boxed Kits & Panels



DELUXE™ BOXED KITS				
Panel/Type	Range(s)	Kit Number:	Notes:	Also Included in Kit:
Boxed Kit				
6-Gauge		82218		Pressure sender Temperature sender Fuel level sender
Speedometer	0-160 MPH		3-3/8" Mechanical	
Tachometer	8,000 RPM		3-3/8" Electric	
Oil Pressure	0-100 PSI		2-1/16" Electric	
Water Temp	100-280°F		2-1/16" Electric	
Fuel Level	240 Ohm		2-1/16" Electric	
Voltmeter	10-16V		2-1/16" Electric	

Kit includes: Light kits, installation instructions and additional accessories as indicated above.

2-1/16" DELUXE™ CHROME PANELS				
Panel/Type	Range(s)	Kit Number:	Notes:	Also Included in Kit:
Double Panels				
Oil Pressure/ Water Temperature	0-100 psi/ 100-265°F	873137	Electric	Pressure sender Temperature sender
Oil Pressure/ Water Temperature	5-100 psi/ 100-280°F	873135	Mechanical	6 ft. tubing kit 72" cap. on Water Temp ga.
Triple Panels				
Oil Pressure/ Water Temperature/ Voltmeter	0-100 psi/ 100-280°F/ 10-16V	873136	Electric	Pressure sender Temperature sender
Oil Pressure/ Water Temperature/ Voltmeter	5-100 psi/ 100-265°F/ 10-16V	873134	Mechanical (Voltmeter-electric)	6 ft. tubing kit 72" cap. on Water Temp ga.

Kits include: Mounting panel and hardware, light kits installation instructions and additional accessories as indicated above.

2-5/8" DELUXE™ CHROME PANEL				
Panel/Type	Range(s)	Kit Number:	Notes:	Also Included in Kit:
Triple Panel				
Fuel Pressure/ Oil Pressure/ Water Temperature	1-15 psi/ 5-100 psi/ 100-265°F	82221	Mechanical	2 ea. of 6 ft. tubing kit 72" cap. on Water Temp ga.

Kits includes: Mounting panel and hardware, light kit installation instructions and additional accessories as indicated above.



82218



82221