



Get your original Wings™ today!

Remember the good ol' days when chrome was king and powerful cars ruled the road? When style was just as important as function? If so, we've got the right product for you...original Stewart Warner Wings™. Based on our 1940s style gauges, Wings™ are available with white-on-black, black-on-white, black-on-silver or black-on-cream graphics.

Features include:

- Unique teardrop pointer
- Chrome- or gold-plated bezels with domed lenses
- Classic graphics—instantly recognizable as Stewart Warner's
- Wings™ logo (so you know it's Stewart Warner)
- Available as kits with sending units, or as individual part numbers
- Wings for Truckers™ available (consult your distributor)

SUPER PRIZE PROGRAM

Stewart Warner is a proud sponsor of the National Street Rod Association's Super Prize Program. Earn a chance to win a FREE Gold Wings™ set of instruments at each of the NSRA's shows. Be sure to look for Stewart Warner Wings™ instruments at a distributor near you!





Kit 82225



82472



82474



82664



82660



82478



82482

Kit 82243



82531



82612



82532



82530



82533

Kit 82244



82499



82497



82498



82610



82611

Kit 82222



82659



82661



82473



82477



82471



82481

Kit 82523



82607



82521



82520



82523



82522



Wings™

WINGS™ BOXED KITS			
6-Gauge Kits	Mechanical	Electric	Tach Signal:
Black	82225	82223	Gas/Ign.; 4, 6, 8-Cyl.
White	82224	82222	Gas/Ign.; 4, 6, 8-Cyl.
Electric tachometer (8,000 RPM); electric speedo (160 MPH) & speed sensor; 10-16V voltmeter; 240 Ohm fuel level & sender; 0-80 psi oil pressure (elec kits include pressure sender/mechanical kits include 6 ft. tubing kit w/fittings); 100-240°F water temperature (elec kits include temperature sender/mech kits include 72" capillary tube).			
5-Gauge Kits	Mechanical	Electric	
Black	82227	82229	
White	82226	82228	
Beige	-	82243	
Gold	-	82230	
Silver	-	82244	
Electric speedo (160 MPH) & speed sensor; 10-16V voltmeter; 240 Ohm fuel level & sender; 0-80 psi oil pressure (elec kits include pressure sender/mechanical kits include 6 ft. tubing kit w/fittings); 100-240°F water temperature (elec kits include temperature sender/mech kits include 72" capillary tube)			



Kits include: All kits include mounting hardware, light kits and installation instructions.





Type/Range	Black		White		Beige	Gold	Silver	Additional Kit Needed:
	2-1/16"		2-1/16"		2-1/16"			
	Mech	Elec	Mech	Elec	Elec	Elec	Elec	
Air Pressure 10-150 psi	82488	-	82487	-	-	-	-	114840 (6 ft. tube) or 114841 (16 ft. tube)
Air Suspen. 2-100 psi	82484	-	82483	-	-	-	-	114840 (6 ft. tube) or 114841 (16 ft. tube)
Boost 40 psi/30 HG	82492	-	82491	-	-	-	-	114842
Fuel Level 240 Ohm	-	82472	-	82471	82532	82522	82499	See fuel senders page 52
90 Ohm	-	82494	-	82493	-	-	-	
73 Ohm	-	82496	-	82495	-	-	-	
Oil Press 80 psi	82476		82475					114840 (6 ft. tube) or 114841 (16 ft. tube)
		82474		82473	82530	82520	82497	279A
Oil Temp 140-320°F	-	82490	-	82489	-	-	-	280EE-F
Pyrometer ⁴ 300-1500°F	-	82486	-	82485	-	-	-	See page 53 for probes
Water Temp 100-240°F	-	82478	-	82477	82531	82521	82498	280EC
	100-265°F							
	72" cap.	82480-72		82479-72				
	96" cap.	82480-96		82479-96				
144" cap.	82480-144		82479-144					
Voltmeter 10-16V	-	82482	-	82481	82533	82523	82610	
	3-3/8"		3-3/8"					
Tachometer 8,000 RPM	-	82660	-	82659	82613	82608	82614	4, 6, 8-cylinder
3,500 RPM	-	82672 ¹	-	82671 ¹	-	-	-	See note 1 below
3,500 RPM	-	82674 ²	-	82673 ²	-	-	-	See note 2 below
Speedometer 80 MPH	82666	-	82665	-	-	-	-	
120 MPH	-	82670 ³	-	82669 ³	-	-	-	See note 3 below
160 MPH	82664		82663					
		82662 ⁴		82661 ⁴	82612 ⁴	82607 ⁴	82611 ⁴	See note 4 below

Kits include: Mounting hardware, light kit (bulb & socket), installation instructions. Purchase senders or tubing separately.

¹ Programmable for alternator or order sender 114878 for mechanical take-off applications

² For tone/flywheel applications and requires sender 82674

³ Senders: Mechanical take-off applications require sender 82527; Tone/Flywheel applications require sender 82646

⁴ Senders: Mechanical take-off applications require sender 114878; Tone/Flywheel applications require sender 82646