

Rating	20A 12VDC		
Contact Resistance	50m ohm Max.		
Insulation Resistance	DC 500V 100M ohm Min.		
Dielectric Strength	AC 1500V 1 minute		
Operation Temperature	-25°C~+85°C		
Circuit	3P SPST ON-OFF (LED)		

**MATERIAL:**  
Frame:Black, PA#66  
Rocker:Black, PA#66  
LED:Green light

**Diagram**

OFF

ON

Dimensions (mm):

- Top diameter:  $\phi 23.0 \pm 0.3$  [ $\phi 0.906$ ]
- Top width:  $2.0 \pm 0.1$  [0.079]
- Top offset:  $3.9 \pm 0.5$  [0.154]
- Top height:  $2.0 \pm 0.3$  [0.079]
- Terminal 3 offset:  $0.8 \pm 0.05$  [0.031]
- Terminal 2 offset:  $7.1 \pm 0.3$  [0.280]
- Terminal 1 offset:  $8.3 \pm 0.5$  [0.327]
- Terminal height:  $14.5 \pm 0.3$  [0.571]
- Bottom diameter:  $\phi 19.8 \pm 0.3$  [ $\phi 0.780$ ]
- Bottom height:  $10.7 \pm 0.2$  [0.421]
- Bottom offset:  $\phi 2.2 \pm 0.2$  [ $\phi 0.087$ ]
- Bottom width:  $4.75 \pm 0.1$  [0.187]

C8\DEL CITY\7520015(R13-112B9-02)

						△
						△
<b>Date</b>	<b>Name</b>	<b>Description</b>				<b>NO</b>
<b>Drawing</b>	<b>Check</b>	<b>Approval</b>	<b>SCI No.</b>		<b>Model Name</b>	ROCKER SWITCH
			<b>DEL CITY P/N</b>	7520015	<b>Model No.</b>	R13-112B9-02-BBG
04/18/'07	04/18/'07		<b>Unit</b>	mm		