


ITEM NUMBER	DESCRIPTION	COLOR	AMPERAGE
74703	AUTO RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, VIOLET, 3 AMP, 14V	VIOLET	3 AMP
74705	AUTO RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, LIGHT BROWN, 5 AMP, 14V	LIGHT BROWN	5 AMP
74706	AUTO RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, MOSS GREEN, 6 AMP, 14V	MOSS GREEN	6 AMP
74775	AUTO RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, BROWN, 7.5 AMP, 14V	BROWN	7.5 AMP
74710	AUTO RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, RED, 10 AMP, 14V	RED	10 AMP
74715	AUTO RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, BLUE, 15 AMP, 14V	BLUE	15 AMP
74720	AUTO RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, YELLOW, 20 AMP, 14V	YELLOW	20 AMP
74725	AUTO RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, WHITE, 25 AMP, 14V	WHITE	25 AMP
74730	AUTO RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, GREEN, 30 AMP, 14V	GREEN	30 AMP

	TOLERANCE UNLESS OTHERWISE SPECIFIED	
	0 > mm ±	ANGLE
		0° > ° REF ±
STUD SIZE	14VDC (MANUAL IS 32VDC)	
MATERIAL	TIN-PLATED COPPER ALLOY	
TERMINATION	5.2MM WIDE BLADES	
OPERATING TEMPERATURE	-40 F - 185 F (-40 C - 85 C)	
INTERRUPT RATING	2000A AT 28VDC	
CERTIFICATIONS	UL 1500, ISO10924-4, SAE J553 AND J1171 (IGNITION PROTECTED)	