


ITEM NUMBER	DESCRIPTION	COLOR	AMPERAGE
74905	MODIFIED RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, LIGHT BROWN, 5 AMP	LIGHT BROWN	5 AMP
74906	MODIFIED RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, MOSS GREEN, 6 AMP	MOSS GREEN	6 AMP
74975	MODIFIED RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, BROWN, 7.5 AMP	BROWN	7.5 AMP
74910	MODIFIED RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, RED, 10 AMP	RED	10 AMP
74915	MODIFIED RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, BLUE, 15 AMP	BLUE	15 AMP
74920	MODIFIED RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, YELLOW, 20 AMP	YELLOW	20 AMP
74925	MODIFIED RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, WHITE, 25 AMP	WHITE	25 AMP
74930	MODIFIED RESET LOW PROFILE ATC/ATO® CIRCUIT BREAKER, BLADE STYLE, GREEN, 30 AMP	GREEN	30 AMP

	TOLERANCE UNLESS OTHERWISE SPECIFIED	
	0 > mm ±	ANGLE
		0° > ° REF ±
STUD SIZE	14VDC (MANUAL IS 32VDC)	
MATERIAL	TIN-PLATED COPPER ALLOY	
TERMINATION	5.2MM WIDE BLADES	
OPERATING TEMPERATURE	-40 F - 185 F (-40 C - 85 C)	
INTERRUPT RATING	2000A AT 28VDC	
CERTIFICATIONS	UL 1500, ISO10924-4, SAE J553 AND J1171 (IGNITION PROTECTED)	